

Proliferation of GPS/GNSS Jammer Devices

Disclaimer

The views and opinions expressed herein do not necessarily reflect the official policy or position of any government agency

Jamming vs. Spoofing

- Jamming is intended to <u>prevent</u> a receiver from acquiring, tracking, or navigating with GNSS signals
- Spoofing is intended to <u>fool</u> a receiver so it provides false position, navigation, and/or time (PNT)
 - Thus allowing the Spoofer to control the victim's PNT
- Smart-Jamming is intended to cause receivers to <u>acquire false signals</u>, which either:
 - Prevents navigation (with less power than for jamming),
 - Or, causes false (but uncontrolled) PNT results



What Are Jammers?

Generally includes devices commonly called signal blockers, GPS jammers, cell phone jammers, text blockers, etc

- Illegal radio frequency transmitters
- Designed to block, jam, or otherwise interfere with authorized radio communications











How do jammers work?


- A jammer can *block all radio communications* on any device that operates on radio frequencies within its range.
- *Emits radio frequency waves* that prevent the targeted device from establishing or maintaining a connection.
- Generally *does not discriminate* between desirable and undesirable communications.
- Jammers can:

prevent your cell phone from making or receiving calls, text messages,
 and emails;

- prevent your Wi-Fi enabled device from connecting to the Internet;
- prevent your GPS unit from receiving correct positioning signals; and
- prevent a first responder from locating you in an emergency.




Received GPS Signals are Weak



GPS defines the minimum C/A "open sky" signal power to be -158.5 dBW, 11 times weaker than calculated here

- Signals from each GPS satellite cover 38% of the earth or 194,244,017 sq km
- A 50 watt GPS transmitter thus provides ~2.6E-13 Watts per square meter on the earth
- A hemispheric L1 antenna "capture area" is ~0.006 m
- Received signal power thus is
 ~1.5E-15 Watts (-148 dBW)
 or ~1.5E-12 mW (-118 dBm)
- Very weak signals!!!

The Near/Far Problem




Jamming Sources

- Thrill seekers interrupt GPS "for the fun of it"
- "Privacy" jammers, e.g., cigarette lighter devices
- Criminals
- Terrorists
- Government authorized services
 - Powerful adjacent channel signals causing overload
 - Higher order intermodulation products, e.g., $2f_1 f_2$





Jammers for Sale



Thank You

Questions?